



HUSKY 8

Heavy-Duty four-tracked carrier.

FOREMOST

HUKSY 8

PERFORMANCE

Weights

Payload	80,000 lbs	36,287 kg
Tare	94,500 lbs	42,864 kg
Gross Vehicle Weight	174,500 lbs	79,152 kg
Turning Radius	46'	14 m
Maximum Speed	9 mph	14.5 km/h
Fording Depth	56 in	1,422 mm
Maximum Gradeability	Side 40%	Forward 60%

GROUND PRESSURE at 6 in (150 mm) PENETRATION

Load	Pressure
0 tons (0 kg)	2.50 psi (17.2kPa)
10 tons (9,072 kg)	3.03 psi (20.9 kPa)
20 tons (18,144 kg)	3.56 psi (24.6 kPa)
30 tons (27,216 kg)	4.09 psi (28.2 kPa)
40 tons (36,287 kg)	4.62 psi (31.9 kPa)

ENGINE

Make	Caterpillar	
Model	C13	
Type	Diesel, turbo, electronic fuel control	
Cylinders	6	
Displacement	12.5 L	763 in ³
Horsepower @ 2,100 rpm	440 hp	328 kW

DRIVE TRAIN

Transmission

Make	Allison 4500 RDS
Type	Automatic, electronic controlled, 5th and 6th blocked, retarder available

SUSPENSION

Front Undercarriage

Type	Torsional Coil Spring
Hubs	Oil bath, metal face seals

Rear Undercarriage

Type	Walking Beam
Hubs	Oil bath, metal face seals

CAPACITIES

Fuel Tank	180 US gal	681 L
-----------	------------	-------

WHEELS

10:00 x 20 - 14ply, permafilled

TRACKS

Type	D-dent	
Width	56"	1,422 mm
Belt Width	20"	508 mm
Belt Ply	7 ply	

ELECTRICAL SYSTEM

Voltage	12V	
Alternator Capacity	160 A	
Battery Capacity	2 x 8D batteries, 1,450 CCA 2,900 CCA reserve	

DIMENSIONS

Basic Unit

Overall Length	581 in	14,757 mm
Overall Width	143 in	3,632 mm
w/o Tracks	108 in	2,743 mm
Overall Height	175 in	3,810 mm
Ground Clearance	21"	533 mm

Deck

Deck Height	69"	1,753 mm
Deck Length	412 in	10,465 mm
Deck Width	108	2,743 mm

OPTIONAL EQUIPMENT

Air conditioning	Arctic package	Strobe light
Deck and oilfield winches	Custom hydraulics	
Cab - 1 man, 2 man, 6 man	Frame extension	

Deck

Dual Rotary Drills	Excavators
Drills	Cranes - knuckle, stiff boom
Service rigs	

